



Product Specification Guide

Product Name:

LIMESTONE PLASTER – LOW SHEEN

PRODUCT DESCRIPTION: Natural mineral based plaster produces the matte, smooth finish on walls and ceilings.

- Limestone Plaster made with highest quality all natural ingredients, produces matte-to-low sheen finish (depending on the application).
- Achieve smooth, or fine-textured natural stone effect on interior surfaces.
- Finish creates a timeless multi-toned stone look with subtle, elegant mottling.
- Product comes in ready to use, smooth paste, in a curated color palette. Can be also custom tinted to a desired color.
- Manufactured in USA with highest quality all natural ingredients, and non-toxic formula. Hypo allergenic, produces a healthy indoor living environment, LEED point qualified.

READ ALL INSTRUCTIONS THOROUGHLY BEFORE USE

COVERAGE: 1-Gallon will cover approximately 80 sq ft in one coat. Recommended application is in two or more coats.

APPLICATION: Make sure walls are dust and debris free, and substrates are flat, smooth, cohesive, and uniform in consistency. Surface should be smooth to a minimum of level 3 drywall finish. Prime with Color Atelier Bonding Primer whether new drywall or painted wall or restored surfaces. If tinting the product, use universal tints, or zero VOC pigments. Mix the product thoroughly before use to ensure consistency. Apply the first coat of Limestone Plaster with a trowel, as evenly as possible avoiding trowel lines and ridges. Apply the second coat after the first coat is completely dry, this coat is where you can create some kind of a troweled texture, if desired. Apply the second coat using slight pressure while applying product with trowel. You may polish the limestone plaster finish to a satin like-sheen or leave it matte. Sealing or waxing is optional.

Matte finish: On last the coat, as the plaster dries, do not burnish the plaster.

Polished finish: On the last coat, as the plaster dries, burnish plaster with edge of trowel obtaining a smooth surface and satin-like finish. Wax can be applied for an even higher polish.

Top coats: If desired, Limestone Plaster can be finished with Sealer, or Wax.

Limewash: Limewash Paint can be applied in a thin manner on top of Limestone Plaster for subtle or dramatic decorative color finishes.

NOTE: Do not apply when surface or ambient temperature is below 41 degrees Fahrenheit or above 93 degrees Fahrenheit.

DRYING TIME: Allow to dry 24 hours between coats.

CLEAN UP: Immediately after use with hot, soapy water.

PACKAGING: Color Atelier Limestone Plaster is available in 1-Gallon & 5-Gallon sizes.

STORAGE: Keep tightly sealed. Store at the room temperature. Do not store outside. Protect from freezing. Rotate stock every 90 days.

OPENING: Cut through slots on lid. Pry lid up at slots. To close, snap lid down firmly. Mix with a drill before decanting or use.

CAUTION: Do not take internally. Close container after each use. MAY IRRITATE EYES. Do not get into eyes. If in eyes, rinse well with water. If swallowed, call Poison Control Centre or doctor immediately.

WARNING: If you scrape, sand or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with HEPA vacuum and wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information at 1-800-424-LEAD or log onto www.epa.gov/lead

NOTICE: We shall not be liable for incidental or consequential damages, directly or indirectly sustained, nor for any loss caused by application of these goods not in accordance with current printed instructions or for other than the intended use. Our liability is expressly limited to replacement of defective goods. Any claim shall be deemed waived unless made in writing to us within 30 days from the date it was or reasonably should have been discovered.

KEEP OUT OF REACH OF CHILDREN

