



Product Specification Guide

Product Name:

COLOR ATELIER MATTE SEALER

PRODUCT DESCRIPTION: Color Atelier Matte Sealer is a clear, matte protective coat that is suitable for plaster and stone surfaces. It is non-toxic, and water based, provides super durable, natural finish. It is designed to protect, and highlight the surface's natural appearance, without affecting its color or finish. When Color Atelier Matte Sealer is polished, it gives the surface a satin finish.

READ ALL INSTRUCTIONS THOROUGHLY BEFORE USE

COVERAGE: One Quart will cover approximately 200 to 300 square feet.

APPLICATION: After all painting and burnishing is completed, you may seal the walls. Make sure the walls have dried and cured for at least 24 hours. Stir the sealer thoroughly prior to use. Simply apply the sealer with a lime brush in a random or "crows feet" method, and brush the sealer on section by section, back wipe any excess and rub in using a circular motion with a lint free cloth. The process is simple and quick, simply do not over work it. One or two coats of sealer are recommended. Allow sealer to dry for a couple of hours in between coats. Polish again with a dry cloth just as the last coat dries. Darkens color until dry
Stir it thoroughly prior to use. Allow surfaces to dry for up to 48 hours before applying the Matte Sealer.

SURFACE PREPARATION: All surfaces must be firm, dry, and cleaned free of dust, dirt.

COLOR: Appears milky white in can, dries clear. Always perform a test sample before use as a slight color variation may occur.

MAINTENANCE: Remove surface dust to clean. To renew protection, apply the product every two to three years

NOTE: Storage temperature: from 41 °F to 86 °F.

Do not apply when surface or ambient temperature is below 50 °F or above 86 °F.

DRYING TIME: Allow to dry 2 hours between coats.

CLEAN UP: Immediately after use with hot, soapy water.

PACKAGING: Color Atelier Matte Sealer is available in Quart size.

TECHNICAL FEATURES:

Color: Appears milky white in can, dries clear. Always perform a test sample before use as a slight color variation may occur.

Odor: light

Relative Density: 1.000 Kg/l

Flash point: 199.4 °F (> 93°C)

OPENING: Cut through slots on lid. Pry lid up at slots. To close, snap lid down firmly. Stir it well before decanting or use.

CAUTION: Do not take internally. Close container after each use. Do not get into eyes. If in eyes, rinse well with water. If swallowed, call Poison Control Centre or doctor immediately.

NOTICE: We shall not be liable for incidental or consequential damages, directly or indirectly sustained, nor for any loss caused by application of these goods not in accordance with current printed instructions or for other than the intended use. Our liability is expressly limited to replacement of defective goods. Any claim shall be deemed waived unless made in writing to us within 30 days from the date it was or reasonably should have been discovered.

KEEP OUT OF REACH OF CHILDREN.

