



## Product Specification Guide

**Product Name:** COLOR ATELIER BONDING PRIMER FOR PLASTER

---

**PRODUCT DESCRIPTION:** Mineral based, high solid, interior & exterior bonding primer. It adds tooth to the surface, is designed to mineralize synthetic, or unstable substrates prior to plaster applications, including Color Atelier Limestone Plaster, and Tadelakt. It is a premium quality essential primer contains marble dust and other minerals, designed for use with plasters to achieve a more consistent appearance and uniform absorption.

- Matte finish
- Thicker consistency, easy application with roller
- Odorless
- Low VOC
- Water thinned
- Fast drying
- Can be used on wood
- The natural state of the primer is white, may be tinted with universal liquid pigments if required.

## READ ALL INSTRUCTIONS THOROUGHLY BEFORE USE

**APPLICATION:** Stir, shake thoroughly prior to use. Apply one or two coats with a roller. Allow minimum 6 hours dry time in between coats.

**COVERAGE:** Product is sold by weight.  
14 lbs covers approximately 150 to 200 sq. ft.  
50 lbs covers approximately 525 to 700 sq. ft.  
Dry mil thickness: 1.4 mils/

**COLOR:** The natural state of the primer is white, may be tinted with universal liquid pigments if required.

**PACKAGING:** Color Bonding Primer for Plaster is available in 1-Gallon and 5-Gallon size.

**SURFACE PREPARATION:** For best results, all surfaces must be cleaned thoroughly, cured, firm and dry. Also free from dust, dirt and oil. Newly completed walls should be left to cure before the application of Lime Primer.

**NOTE:** Do not apply if air or surface temperature is below 50 °F or is likely to fall below 50 °F within 2

hours of application.

**DRYING TIME:** 2 hours to dry. At 77 °F and 50% Relative humidity.

**CLEAN UP & THINNING:** Use Water. Clean brushes, rollers, pads etc. with warm, soapy water immediately after completion of painting. Dry empty containers may be recycled in a can recycling program. Local disposal requirements vary; see your local dealer and consult your sanitation department or state-designated environmental agency on disposal options in your area.

**CAUTION:** Do not take internally. Close container after each use. MAY IRRITATE EYES. Do not get into eyes. If in eyes, rinse well with water. If swallowed, call Poison Control Centre or doctor immediately.

**WARNING:** If you scrape, sand or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with HEPA vacuum and wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information at 1-800-424-LEAD or log onto [www.epa.gov/lead](http://www.epa.gov/lead)

**NOTICE:** We shall not be liable for incidental or consequential damages, directly or indirectly sustained, nor for any loss caused by application of these goods not in accordance with current printed instructions or for other than the intended use. Our liability is expressly limited to replacement of defective goods. Any claim shall be deemed waived unless made in writing to us within 30 days from the date it was or reasonably should have been discovered.

**KEEP OUT OF REACH OF CHILDREN**

**NOTICE:** We shall not be liable for incidental or consequential damages, directly or indirectly sustained, nor for any loss caused by application of these goods not in accordance with current printed instructions or for other than the intended use. Our liability is expressly limited to replacement of defective goods. Any claim shall be deemed waived unless made in writing to us within 30 days from the date it was or reasonably should have been discovered.

