



Product Specification Guide

Product Name:

LIMESTONE PLASTER – LOW SHEEN

PRODUCT DESCRIPTION: Natural mineral based plaster produces the matte, smooth finish on walls and ceilings.

- Limestone Plaster made with highest quality all natural ingredients, produces matte-to-low sheen finish.
- Achieve smooth, natural stone effect on interior surfaces.
- Finish creates a timeless multi-toned stone look with elegant mottling.
- Product is available in natural color, can be custom tinted to any desired color.
- Manufactured in USA with highest quality all natural ingredients, and non-toxic formula. Hypoallergenic, produces a healthy indoor living environment, LEED point qualified.

READ ALL INSTRUCTIONS THOROUGHLY BEFORE USE

COVERAGE: One gallon will cover approximately 70 to 80 square feet, depending on porosity of surface.

INSTRUCTIONS FOR USE: Restore and repair walls to smooth surfaces. Prime with Color Atelier primer or your choice of water based primer whether new drywall or plaster, or restored surfaces.

TINTING AND APPLICATION: Make sure walls are dust and debris free, and substrates are flat, smooth, cohesive, and uniform in consistency. Surface should be smooth to a minimum Level 4, or preferably Level 5 finish. Tint the product with universal tints, or zero VOC pigments. Apply one coat of Limestone Plaster with a trowel. Allow 24 hours drying time. Apply second coat using slight pressure while applying product with trowel. Polishing the finish plaster is not recommended as this product is designed for creating matte, natural stone look. Sealing or waxing is optional.

NOTE: Do not apply when surface or ambient temperature is below 41 degrees Fahrenheit or above 93 degrees Fahrenheit.

DRYING TIME: Allow to dry 24 hours between coats.

CLEAN UP: Immediately after use with hot, soapy water.

PACKAGING: Color Atelier Limestone Plaster is available in Gallon & 5-Gallon sizes.

STORAGE: Keep tightly sealed. Store at the room temperature. Do not store outside. Protect from freezing. Rotate stock every 90 days.

OPENING: Cut through slots on lid. Pry lid up at slots. To close, snap lid down firmly. Mix with a drill before decanting or use.

CAUTION: Do not take internally. Close container after each use. MAY IRRITATE EYES. Do not get into eyes. If in eyes, rinse well with water. If swallowed, call Poison Control Centre or doctor immediately.

WARNING: If you scrape, sand or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with HEPA vacuum and wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information at 1-800-424-LEAD or log onto www.epa.gov/lead

NOTICE: We shall not be liable for incidental or consequential damages, directly or indirectly sustained, nor for any loss caused by application of these goods not in accordance with current printed instructions or for other than the intended use. Our liability is expressly limited to replacement of defective goods. Any claim shall be deemed waived unless made in writing to us within 30 days from the date it was or reasonably should have been discovered.

KEEP OUT OF REACH OF CHILDREN

