



Product Specification Guide

Product Name:

COLOR ATELIER PREP COAT

Mineral-based, tintable, base coat product. Get your walls ready for lime paint, plasters, and topcoat application.

PRODUCT DESCRIPTION: Color Atelier Prep Coat is created for use with lime paint, plasters, and topcoats. This tintable, premium quality base coat product is designed to use for smoothing out the surface or creating texture. Apply one or two coats of Prep Coat with a trowel or a roller depending on the desired texture to achieve. Create a medium to fine texture with a matte or polished finish, depending on application technique. Prep Coat helps achieve a more consistent appearance and uniform absorption of polished lime paint, plasters, top coats, and waxes on interior walls. This premium quality natural mineral based product can be used over previously painted or plastered surfaces. It contains marble aggregates, and easy to handle due to its open time. Manufactured in USA with highest quality ingredients, and non-toxic formula.

READ ALL INSTRUCTIONS THOROUGHLY BEFORE USE

COVERAGE: One gallon will cover approximately 100 square feet, depending on porosity of surface.

INSTRUCTIONS FOR USE: Restore and repair walls to smooth surfaces, or leave them with texture and defects for an older looking, distressed finish. Color Atelier Prep Coat can be used directly over on previously painted and plastered surfaces. Only prime walls with a water-based primer if the walls previously finishes with oil based coatings. Tinting the prep coat is optional. Apply one coat of product with a stainless steel trowel. You can apply the second coat as soon as the first coat is completely dry. You can lightly sand the walls with a fine sanding pad after the second coat is dry. Alternatively you can use a roller to apply the Prep Coat whether smooth or with textured effects. Prep Coat will dry to a matte to low sheen finish, you may leave it as it is or finish it with lime paint, plaster, wax and or a topcoat.

NOTE: Do not apply when surface or ambient temperature is below 41 °F or above 93 °F.

DRYING TIME: Allow to dry 24 hours between coats.

CLEAN UP: Immediately after use with hot, soapy water.

PACKAGING: Color Atelier Prep Coat is available in Gallon & 5-Gallon sizes.

STORAGE: Keep tightly sealed. Store at the room temperature. Do not store outside. Protect from freezing. Rotate stock every 90 days.

OPENING: Cut through slots on lid. Pry lid up at slots. To close, snap lid down firmly. Mix with a drill

before use.

CAUTION: Do not take internally. Close container after each use. MAY IRRITATE EYES. Do not get into eyes. If in eyes, rinse well with water. If swallowed, call Poison Control Centre or doctor immediately.

WARNING: If you scrape, sand or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with HEPA vacuum and wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information at 1-800-424-LEAD or log onto www.epa.gov/lead

NOTICE: We shall not be liable for incidental or consequential damages, directly or indirectly sustained, nor for any loss caused by application of these goods not in accordance with current printed instructions or for other than the intended use. Our liability is expressly limited to replacement of defective goods. Any claim shall be deemed waived unless made in writing to us within 30 days from the date it was or reasonably should have been discovered.

KEEP OUT OF REACH OF CHILDREN

